



Cast Iron Rotary Twin Gear Pump



Technical Specification Table:-

MODEL RSRTS/RSRTL	SUCTION & DELIVERY SIZE	CAPACITY AT 1440 RPM		
		LPM	US GPM	M ³ /Hr
RSRT-50-S	1/2" x 1/2"	8.30	2.20	0.50
RSRT-50-L	1/2" x 1/2"	25.00	6.60	1.50
RSRT-100-S	1" X 1"	33.30	8.80	2.00
RSRT-100-L	1" X 1"	50.00	13.20	3.00
RSRT-150-S	1 1/2" X 1 1/2"	83.30	22.00	5.00
RSRT-150-L	1 1/2" X 1 1/2"	125.00	33.30	7.50
RSRT-200-S	2" X 2"	150.00	39.00	9.00
RSRT-200-L	2" X 2"	200.00	52.80	12.00
RSRT-250-S	2 1/2" X 2 1/2"	250.00	52.80	15.00
RSRT-250-L	2 1/2" X 2 1/2"	333.30	88.00	20.50
RSRT-300-S	3" X 3"	415.00	105.00	25.50
RSRT-300-L	3" X 3"	500.00	132.00	30.50
RSRT-400-S	4" X 4"	599.76	158.40	36.50
RSRT-400-L	4" X 4"	833.30	220.00	50.50
RSRT-500-S	5" X 5"	1000.00	264.00	60.50
RSRT-500-L	5" X 5"	1499.00	396.00	90.50
RSRT-600-S	6" X 6"	1660.00	440.00	100.50
RSRT-600-L	6" X 6"	2083.00	500.00	125.50

NOTE: All dimensions are in millimeters. Unless otherwise stated Specifications are subject to change without prior notice as improvement are made from time to time.

Conversion: 1 Imperial Gallon = 4.5 Liters / 1 U.S. Gallon = 3.78 Liters / 1 P.S.I. = 2.31 Feet. / 1 Kg/cm² = 14.2 P.S.I.