



Fuel Injection Internal Gear Pump

Technical Specification Table:-

Model	Capacity In LPH At 1440 RPM	Suction & Delivery Size	Motor H.P.	
			3 Kg/CM2	30 kg/CM2
RSIG-15	150 LPH	1/2"X 1/2"	0.25	1.50
RSIG-30	300 LPH	1/2"X 1/2"	0.25	1.50
RSIG-45	450 LPH	1/2"X 1/2"	0.25	2.00
RSIG-60	600 LPH	1/2"X 1/2"	0.25	2.00
RSIG-100	1000 LPH	3/4"X 3/4"	0.75	3.00
RSIG-150	1500 LPH	3/4"X 3/4"	0.75	3.00
RSIG-200	2000 LPH	3/4"X 3/4"	0.75	5.00
RSIG-250	2500 LPH	3/4"X 3/4"	0.75	5.00
RSIG-300	3000 LPH	1"X 1"	1.50	7.50
RSIG-450	4500 LPH	1"X 1"	1.50	10.0
RSIG-600	6000 LPH	1"X 1"	1.50	10.0

NOTE: All dimensions are in millimeters. Unless otherwise stated Specifications are subject to change without prior notice as improvement are made from time to time.

Conversion: 1 Imperial Gallon = 4.5 Liters / 1 U.S. Gallon = 3.78 Liters / 1 P.S.I. = 2.31 Feet. / 1 Kg/cm² = 14.2 P.S.I.